

3 Mega Pixel Torpedo



Features

- 3 Mega Pixel IP Camera
- Outdoor IR Torpedo
- 40IRs, 100ft Range
- 2.8~12mm Auto Iris
- ICR
- PoE(DC48V) , DC12V



3rd Party NVR Support



Auto Iris



3D NR



Wide Dynamic Range



Varifocal



3-way Gimbal



Infrared



POE Compliant



Day & Night



IP66 Weather-Proof



Specification

Model Name	SCOPE212WIR3
Image Sensor	1/2.8" Sony Exmore 3MP Image Sensor
Effective Pixel	2048(H) x 1536(V), 3.14 Mega Pixels
Scanning System	Progressive Scan
Resolution	2048x1536, 1600x1200, 1920x1080,1280x1024, 1280x960, 1280x 720, 1024x768, 640x480, 320x240
Day & Night	Auto/Day(Color)/Night(B/W)
Privacy Zone	On/Off(6 Programmable Zone)
WDR	WDR (5 step)
IR	40IRs, 100ft Range, On/Off
Lens	2.8~12mm Auto Iris Mega Pixel Lens
DNR	Digital Noise Reduction(1~63)
Motion Detection	48 Zone(On/Off, 1~5 step)
Shutter Speed	Auto(1/15~1/10000), Suppress Rolling, Manual , License Plate Capture Mode
White Balance	Auto, Indoor/Outdoor/Fluorescent
Ext. video	VBS 1.0Vp-p
Sense Up	Auto(1~6 Step)
System O/S	Embedded Linux
Network	RJ45 100/100 Base-T PoE
Network Protocol	TCP/IP, UDP/IP, RTS, RTSP, RTCP, NTP, HTTP,DHCP, FTP, SMTP, DNS, DDNS
Onvif	Ver. 2.0
Video format	H.264, MPEG4, MJPEG Triple Stream
Frame Rate	5~15fps
Audio	G.711 u-law, Two way
Event	Sensor In x 1ea, Alarm Out x1ea
Power	PoE(DC48V), DC12V
Current Consumption	Max. 800mA
Operation Temperature	14°F~122°F
Dimension	3" x 3.2" x 13"
Weight	2 lb