

HT212VIR2



Features

- HD 1080P Video Output
- Adopt HD TVI Technology
- True Day/Night
- 2.8 ~ 12mm vari-focal lens
- OSD menu, 3D DNR, Smart IR
- Up to 120ft IR distance
- IP66 weatherproof & Vandal Proof
- Up the Coax(via coaxial cable)
- 120 dB Wide Dynamic Range
- Dual Voltage 12VDC/24VAC

Specification	Detail
Image Sensor	1/3" Progressive Scan CMOS
Signal System	PAL/NTSC
Effective Pixels	1920(H) x 1080(V)
Min. Illumination	0.01 Lux @(F1.2, AGC ON), 0 Lux with IR / 0.014Lux @(F1.4, AGC ON), 0 Lux with IR
Shutter Speed	1/25(1/30)s to 1/50,000s
Lens	2.8 ~ 12mm @ F1.4 Angle of View : 92° ~ 32°
Angle Adjustment	Pan:0~355°, Tilt:0~80°, Rotation:±90°
Day & Night	ICR
Wide Dynamic Range	120dB
Video Frame Rate	1080p@25fps / 1080p@30fps
HD Video Output	1 Analog HD output
CVBS Output	1 Vp-p Composite Output(75Ω /BNC)
S / N Ratio	More than 52dB
Scene	Indoor, Outdoor, Indoor1, LOW-LIGHT
Camera ID	On/Off (15 characters, position programmable)
AGC	Support
D/N Mode	Color/BW/EXT
White Balance	ATW, AWC-SET, Indoor, Outdoor, Manua
Privacy Mask	On/Off, maximum 8 zones
Motion Detection	On/Off, maximum 4 zones
BLC	Support
Anti-flicker	On/Off
Language	English, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and Arabic
Function	Eclipse, Digital noise reduction, Digital zoom(62x), Slow Shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM
Working Temperature / Humidity	-20°C ~ 60°C (-4°F ~ 140°F) / Humidity 90% or less (non-condensing)
Power Supply	12 VDC / 24VAC
Power Comsumption	12 VDC : Max.4.5W / 24VAC:Max. 6.5W
Weather Proof Ratings	IP66
Impact Protection	IEC60068-2-75 test, Eh, 20J, EN50102, up to IK10.
IR Range	Up to 120 ft
Communication	Up the coax (need UTC controller) / Protocol : Pelco-C(Coaxitron)
Dimensions	φ145.3 × 124.2 mm (φ5.72" × 4.89")
Weight	880g(1.95lbs)